

#### Reliable special designed instrument





Standard configuration				
Horn	Front combo lights	Speed-limiting valve		
Three-spool control valve	Transmission oil filter	Lifting and tilting operation lever		
3-stage full free lift mast	Rear combo lights	Tow pin		
Power steering	Back-up alarm	Overhead guard		
Semi-suspension seat	Overhead guard rain cover	Combined display		
Load backrest	Standard forks	LPG Low Fuel Indicator		
Rear view mirror	Integrated electric box			

Optional						
Max. speed control system	Lifting OPS control system	LED headlights				
LED Rotating Light	Torque converter oil temperature meter	No hand brake alarm				
Dual Air Filter	Optional attachments	Rear grab handle with horn button				
Hydraulic Fork Positioner	Rotating seat for LPG					
Rear work light	Swing Out/Drop-Down LPG Bracket					



### **HELI AMERICA INC**

ADD: 4025 Welcome All Road, Suite 150 Atlanta, GA30349, U.S.A. E-MAIL:heli@heliforkliftamerica.com TEL: 404-242-3288



# **CP(Q)YD15-20C** 3000-4000lbs (1.5-2.0t) H3C IC Cushion Tire Forklift

www.heliforkliftamerica.com

## CP(Q)YD15-20C



### **Heli H3C Series Features**

Improved performance Superior quality

#### Ergonomics

- > Vibration isolators separate the operator compartment from the main frame and the engine/transmission which absorb the truck's vibration for increased operator comfort
- Engine performance and repositioned hydraulic pump offer quieter and smoother operation and less noise
- Improved hydraulic control functions also reduce noise and increase performance

### **Operator Comfort - Visibility**

- Operator compartment has been enhanced by creating more foot and leg room with plenty of head room under the overhead guard
- Visibility has been improved with narrower mast channels and more open overhead guard
- Higher contrast LED display makes it easier to see in all lighting conditions
- Comfortable suspension seat is standard with full adjustment for different operators
- Low, wide step and grab handle make for easy entry to operator's compartment
- Controls and park brake are within easy reach to reduce operator strain



#### Increased Productivity

- Smaller turning radius and hydraulic power steering makes for tighter turns and easier steering operation
- Reliable powershift transmission relieves operator from constantly shifting transmission
- > H3C series hydraulic performance has been enhanced for maximum productivity
- Ergonomically designed operator's compartment enhances operator productivity, as well as providing safety and comfort

#### Improved Performance

- All aluminum radiator increases air flow and dissipates heat more efficiently
- Smaller steering wheel with fewer turns lock-to-lock for quicker turns 35% faster lifting speeds over previous generations
- > Lifting cylinders are damped to reduce noise and provide smoother operation
- Heavy duty powertrain offers exceptional performance in all applications

### Serviceability

- Hood opens to an 80 degree angle and floor board is removable for easier access to all important chassis components
- Electrical system, wiring, and hydraulic hoses are convenient and logically laid out with access from above and below
- > All grease points are accessible, including cast steel axle
- Lubrication chart is located on front of operator compartment to highlight essential lubrication requirements

### Safety

- All Heli forklifts for North America meet ANSI B56.1 Safety Standard for Powered Industrial Trucks as well as meeting requirements for CE approval
- All Heli forklifts come standard with Operator Presence System Optional rear grab handle and horn button allows operator to
- safely drive in reverse
- Strobes, Beacons or Blue Lights and Alarms are all available

## CP(Q)YD15-20C

Manufacturers Data and Design Characteristics											
Character											
.01 Manufacturer						HE		r			
.02 Model				CP (Q)YD	15C-KU1H	CP (Q)YD	18C-KU1H	CP (Q)YD2	20CS-KU1H		
04 Rated capacity		lbs	Kg	3000	1350	3500	1600	4000	1815		
5 Load center		in	mm	24	610	24	610	24	610		
06 Operation mode		type	type			Seat	type				
Size											
01 Max.lifting height	Н	in	mm	142	3600	142	3600	142	3600		
Mast overall height(fork to the ground and mast be vertical)	H1	in	mm	83	2110	83	2110	83	2110		
3 Max.fork lifting height(with backrest)	H2	in	mm	183.5	4660	183.5	4660	183.5	4660		
4 Free lift height	H3	in	mm	6	155	6	155	6	155		
05 Overall height(overhead guard)	H4	in	mm	83	2105	83	2105	83	2105		
6 Min.groung clearance (mast/central of body)	H5	in	mm	2.4/3.3	60/83	2.4/3.3	60/83	2.4/3.3	60/83		
7 Distance from the surface of the seat to the overahead guard	H6	in	mm	38.3	974	38.3	974	38.3	974		
8 Traction pin height	H9	in	mm	4.0	100	4.0	100	4.0	100		
9 Backrest height(calculated from the surface of the fork)	H13	in	mm	37.8	960	37.8	960	37.8	960		
Overall length(with fork/without fork)	(L/L')	in	mm	119/82.5	3015/2095	120.3/84	3055/2135	122/85.5	3095/2175		
1 Wheel base	L1	in	mm	50.4	1280	50.4	1280	50.4	1280		
2 Overhang (front/rear)	L2	in	mm	16.7/14.9	425/380	16.7/16.5	425/420	16.7/18.1	430/460		
.3 Overall width	W1	in	mm	37.6	955	37.6	955	37.6	955		
.4 Tread (front tread/rear tread)	(W3/W2)	in	mm	31.5/32.1	800/815	31.5/32.1	800/815	31.5/32.1	800/815		
L5 Fork adjustable range(the external of the fork )(Max./Min.)	W5	in	mm	35/7.9	890/200	35/7.9	890/200	35/7.9	890/200		
6 Min.turning radius(exterior)	r	in	mm	69.3	1740	70.9	1800	72.2	1820		
7 Min.turning radius(exterior)		in	mm	1 9	50	1.9	50	1 9	50		
	Pa	in	mm	121.5	3085	123.8	3145	124.8	3170		
	κα α/β			121.5	5065			124.0	5110		
0 0	α/β L4×W×T	ia		36.2×3.9×1.4	920×100×35	36.2×3.9×1.4	/5° 920×100×35	36.2×4.8×1.6	920×122×40		
20 Fork Size Performance		111.	mm	30.2 ~ 3.5 ~ 1.4	920 ~ 100 ~ 35	50.2 ~ 5.5 ~ 1.4	920×100×35	30.2 ~ 4.0 ~ 1.0	920~122~40		
		mph	Km/h	9.94/9.94	16/16	9.94/9.94	16/16	9.94/9.94	16/16		
01 Max.traveling speed (loaded/unloaded) 02 Lifting Speed (loaded/unloaded)		ft/c	mm/s	21.7/22.8	550/580	21.7/22.8	550/580	21.7/22.8	550/580		
사람들이 이 것은 것은 가장 선생님이 있는 것은 것은 것은 것은 것은 것은 것은 것은 것을 것을 수 있었다. 이 것을 것을 수 있는 것은 것을 가지 않는 것을 수 있는 것을 수 있다. 것을 수 있는 것을 수 있다. 것을 것을 수 있는 것을 수 있다. 것을 것 같이 것을 것 같이 않는 것을 수 있는 것을 수 있다. 것을 것 같이 것을 수 있는 것을 수 있다. 것을 것 같이 것 같이 같이 않다. 것을 것 같이 같이 같이 않다. 것을 것 같이 하는 것 같이 않다. 것 같이 것 같이 않는 것 같이 않다. 것 같이 않는 것 같이 않는 것 같이 않다. 것 같이 않는 것 같이 않다. 것 같이 하는 것 같이 없다. 것 같이 것 같이 않다. 것 같이 않는 것 같이 않다. 것 같이 않다. 것 같이 없다. 것 같이 않다. 것 같이 않다. 것 같이 없다. 것 같이 같이 않다. 것 같이 없다. 것 같이 않다. 것 같이 것 같이 없다. 것 같이 않다. 것 같이 않다. 것 같이 것 같이 없다. 것 같이 않다. 것 않다. 것 같이 않다. 않다. 것 같이 않다. 것 같이 않다. 것 같이 않다.		ft/s				17.7/19.7					
3 Lowing Speed (loaded/unloaded)		IL/S	mm/s KN	17.7/19.7 4496.2/2248.1	450/500	4496.2/2135.7	450/500	17.7/19.7	450/500		
4 Max.drawbar pull (loaded/unloaded)		101 06	NN 04		20/10		20/9.5	4496.2/2135.7	20/9.5		
05 Max.gradeability (loaded/lnloaded)		90	%0	35,	20	32,	/20	30	/20		
Weight		II. 2	И-	6657.0	2020	7105	2250	7005.0	2450		
1 Total weight		lbs	ng	6657.9	3020	7165	3250	7605.9	3450		
2 Weight distribution loaded (front/rear)		lbs	Kg	8465.8/1168.4	3840/530	9343.2/1349.2	4238/612	10031/1543.2	4550/700		
Weight distribution unloaded (front/rear)		lbs	Kg	3097.5/3560.5	1405/1615	2976.2/4188.8	1350/1900	2870.4/4735.5	1302/2148		
Wheel and tyre		1									
01 Wheel number x = drive wheel (front/rear)							/2				
2 Tyre type(front/rear)						cushion tyre,	/cushion tyre				
3 Tyre size(front)				18×6×12							
04 Tyre size(rear)				$14 \times 5 \times 10$							
05 Service brake				Hydraulic-Foot Pedal							
6 Parking brake						Mechanical	-Hand Lever				
Engine Model and Specification											
Model				CPYD15	C-KU1H	CPYD18	C-KU1H	CPYD20	CS-KU1H		
2 Battery(Voltage/Capacity)		V/Ah				12,	/60				
3 Engine mode						Kubota	WG2503				
				LPG: 58.3/2600	LPG: 43.5/2600	LPG: 58.3/2600	LPG: 43.5/2600	LPG: 58.3/2600	LPG: 43.5/2600		
4 Engine rated power		HP/rpm	KW/rpm	Gasoline:57.4/2600	Gasoline:42.8/2600	Gasoline:57.4/2600	Gasoline:42.8/2600	Gasoline:57.4/2600	Gasoline:42.8/2600		
		11 7 7 1 1		LPG: 128.1/1400	LPG: 173.7/1400	LPG: 128.1/1400	LPG: 173.7/1400	LPG: 128.1/1400	LPG: 173.7/1400		
05 Engine rated torque		(lbf.ft)/rpm	Nm/rpm	Gasoline:120.4/1800	Gasoline:163/1800	Gasoline:120.4/1800	Gasoline:163/1800	Gasoline:120.4/1800	Gasoline:163/1800		
06 Engine cylinder number-bore x stroke							4	Automatica de concentra estas de la sega dos del California de la sega da sega de la sega de la sega de la seg No	and a second		
07 Piston displancement		L				2.4	491				
18 Engine fuel tank capacity					2.451						
• Engine fuel tank cabacity											







CP	(Q)YD15C-KU1H
СР	(Q)YD18C-KU1H
CP	(Q)YD20CS-KU1H

**Note:** Capacities shown are reference only. They are computed with mast in vertical position based on 48 inch cube load configuration with center of gravity at true center of cube and standard forks. Longer forks and unusally wide loads can reduce capacity. Consult dealer for any questions about capacities.

Mast type	Max lifting height mm/in	Capacity (load center 500mm)			Overall height			Freelift (with backrest)			Service Weight(unload)		
		CP(Q)YD C 15C	CP(Q)YD 18C Kg/lbm	CP(Q)YD 20C Kg/lbm	CP(Q)YD 15C mm/in	CP(Q)YD 18C mm/in	CP(Q)YD 20C mm/in	CP(Q)YD 15~18C mm/in	CP(Q)YD 20C mm/in	Tilt angle (front/rear) (°)	CP(Q)YD 15C	CP(Q)YD 18C	CP(Q)YD 20C
											kg/lbm	kg/lbm	kg/lbm
ZSM360	3600/142	1350/2976	1600/3527	1800/3968	1750/69	1750/69	1750/69	740/29	745 /29	6/5	545/1202	545/1202	570/1257
ZSM400	4000/157	1350/2976	1600/3527	1800/3968	1885/74	1885/74	1885/74	875/34	880/35	6/5	569/1254	569/1254	597/1316
ZSM435	4350/171	1350/2976	1600/3527	1800/3968	2000/79	2000/79	2000/79	990/39	995/39	6/5	593/1307	593/1307	618/1362
ZSM450	4500/177	1350/2976	1600/3527	1800/3968	2050/81	2050/81	2050/81	1040/41	1045/41	6/5	604/1332	604/1332	629/1387
ZSM470	4700/185	1325/2921	1500/3307	1700/3748	2120/83	2120/83	2120/83	1110/44	1115/44	6/5	620/1367	620/1367	645/1422
ZSM480	4800/189	1300/2866	1400/3086	1650/3638	2150/85	2150/85	2150/85	1140/45	1145/45	6/5	628/1385	628/1385	653/1440
ZSM500	5000/197	1250/2756	1350/2976	1500/3307	2250/89	2250/89	2250/89	1240/49	1245/49	6/5	649/1431	649/1431	674/1486
ZSM540	5400/213	1200/2646	1200/2646	1100/2425	2375/94	2375/94	2375/94	1365/54	1370/54	3/5	674/1486	674/1486	699/1541
ZSM600	6000/236	700/1543	700/1543	900/1984	2600/102	2600/102	2600/102	1590/63	1595/63	3/5	746/1645	746/1645	771/1700

NOTE: 1.5-1.8T: Free lift height (without backrest)+465/17.9mm/in; 2T: Free lift height (without backrest)++465/17.9mm/in;